

PRODUCT DATA SHEET

Sika® Tile Grout®

CEMENTITIOUS GROUT FILLER FOR CERAMIC TILE JOINT

DESCRIPTION

A Tile Grout specially blended from selected high quality performance cements, fillers, pigments and synthetic additive. Only water will be added to provide a creamy paste. When set, the hardened grout paste is mold and mildew resistant. It is necessarily applied in conjunction with Sikafix Tile.

USES

Grout for filling installed ceramic tile joints in bathrooms, swimming pools, kitchens and all other similar applications.

CHARACTERISTICS / ADVANTAGES

- Non-shrink and No Cracks
- Non-Sag/ slump (thixotropic) application
- Water, mildew and mold resistant.
- Mixes with water only and easy to apply
- Available in different colours (see color chart)

PRODUCT INFORMATION

Packaging	25 x 1 kg plastic bag in carton
Shelf Life	One year from date of manufacture
Storage Conditions	Stored in a cool dry place

APPLICATION INFORMATION

Consumption	One (1) square meter requires approx. 0,25 kg of grout powder, depending on type, size and spacing of tiles
--------------------	---

APPLICATION INSTRUCTIONS

MIXING

- Prepare about 0.3 litres of clean tap water in plastic pail. Add the 1 kg of Sika® Tile Grout gradually while mixing until a creamy paste is produced and allow to stand for 10 minutes. Do not use saline or salty water.
- Dampen joints of tiles but without standing water, after the tiles have set overnight.

APPLICATION

- Apply the pasty grout to spaces between tiles (joints) diagonally using a sponge, or small piece of soft cloth. Work the grout paste with enough pressure into the joints and around the edges, filling them uniformly.
- When the residue on tiles begins to form a haze after (about 5 minutes), wipe a wet sponge using same diagonal strokes to the grout applied joints until the grout is flush with the tile surface.
- Wash the sponge, wring out as much water as possible.

sible, then toll the filled joints by lightly running the sponge along the tile grout lines or running the tip of gloved finger or a rounder piece of wood along the grout filled tile joints to level it off with the tiles.

- Wipe any remaining dry residue with a clean soft and dry cloth in order to reveal the tile surface with its true colour and texture.
- Place protective barriers or covering to foot traffic only after at least 24 hours.

LIMITATIONS

Do not mix newly prepared grout paste with an old mix to extend the pot life.

Freshly mixed grout in a pail remains useable up to one hour.

- Do not use saline or salty water. Use only clean or clear lap water
- Do not use absorbent materials as mixing base or container
- Never use acid on other harsh chemicals to remove hardened grout on tile surfaces

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

PT. Sika Indonesia

Jl. Raya Cibinong-Bekasi km.20.

Cileungsi, Bogor 16820 - Indonesia

Tel. +62 21 8230025

Fax. +62 21 8230026

Website: idn.sika.com

email: sikacare@id.sika.com



PRODUCT DATA SHEET

Sika® Tile Grout®

August 2016

020404010010000003